

SKF Technical Bulletin

VKBA 7213



BMW 1 (F20/21), 2 Convertible (F23), 2 Coupe (F22, F87), 3 (F30, F80), 3 Gran Turismo (F34), 3 Touring (F31), 4 Convertible (F33, F83), 4 Coupe (F32, F82), 4 Gran Coupe (F36)



Mandatory replacement of the screws M12 X 1,25 mm included in the kit!



SKF kit	OE Nb
VKBA 7213	31 20 6 794 850, 31 20 6 857 230, 31 20 6 867 256, 31 20 6 876 840

The above-mentioned wheel bearing kit is mounted to the front steering knuckle with four screws. When installing the new SKF wheel bearing VKBA 7213, it is **mandatory** to use the supplied screws **M12 X 1,25** to ensure that the correct thread pitch is matching between the screws and bearing.

VKBA 7213



Pitch: M12x1,25

Always follow the Mounting instructions:

- It is recommended to install the screws first by hand and then finish tightening to specified torque using a torque wrench
- Never use an impact wrench for tightening of the screws
- Always refer to the OE tightening torque specifications

WARNING: Use of wrong screws will destroy the threads and this can result in the loss of the wheel!

YouTube [Click here to watch SKF technical videos on Youtube](#)

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication, but no liability

Flash QR code

