ATF Dex VI

Description:

ATF Dex VI fluid is a low viscosity Automatic Transmission Fluid which is made with a special additive technology, optimized for a wide range of passenger car applications.

Application:

ATF Dex VI is used in an extensive range of European, American and Asian passenger car service fill applications. Additional it can be used in commercial vehicle applications and power steering, too.

Properties:

ATF Dex VI affords following benefits:

- exceptional oxidation behavior
- low viscosity for high fuel economy
- smoother shifts over a long period of time
- excellent anti-rust properties
- low foaming tendency

Specification / Recommendations:

DEXRON VI
Aisin Warner AW-1
Aisin Warner JWS 3324
ASIN Warner AW F8FXX
Bentley PY112995PA
BMW/Mini 83 22 0 142 516
BMW/Mini 83 22 0 397 114
BMW/Mini 83 22 2 163 514 (BMW 8072 B)
Chrysler/Dodge/Jeep 05127382AA
Chrysler/Dodge/Jeep 68043742AA
Daimler / Mercedes MB 236.12, 236.14, 236.41
FORD/Lincoln/Mercury XT-10-QLV [LV]
FORD/Lincoln/Mercury XT-6-QSP or -DSP [SP]
GM/GMC/Opel/Saturn AW1
GM/GMC/Opel/Saturn 88863400, 88863401
Honda/Acura DW-1
Honda 082000-9017 (ATF Type 3.1)
Hyundai/Kia NWS-9638 T-5
Hyundai/Kia SP-IV / SPH-IV
Hyundai/Kia 40000C90SG
Jaguar Fluid 8432
JASO M315, Class 1A
Land Rover TYK500050, LR0022460
Maserati 231603
Mazda FW 6A EL, FW 6AX EL
Mazda FZ
Mercon LV
Mitsubishi ATF-J3
Mitsubishi SP-IV
Nissan/Infinity Matic-S
Porsche 000 043 304 00
Saab 93 165 147 - AW-1
Shell 3353, Shell 134, Shell 1375.4
Toyota/Lexus/Scion WS
VW/Audi G 052 533, G 055 005 (-A, A2)
VW/Audi G 055 540 (A2)

Made in Germany

Typical values:

ATF Dex VI	Unit	Value	Method
Density at 15	kg/m³	844	DIN 51 757
Colour		red	Visuell
Viscosity at 40°C	mm²/s	26,4	DIN 51 562
Viscosity at 100°C	mm²/s	5,6	DIN 51 562
Viscosity Index		160	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flash Point	°C	226	DIN IS0 2592

Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded. Further information is available on the safety data sheet.

Hengst SE
Nienkamp 55-85
48147 Münster · Germany
Tel.: +49 251 20202-0

Made in Germany