ATF Multi Vehicle

Description:

ATF Multi Vehicle fluid is an Automatic Transmission Fluid which is made by multi-vehicle anti-shudder additive technology optimized for passenger car applications.

ATF Multi Vehicle affords following benefits:

- exceptional oxidation behavior
- anti-shudder durability
- smoother shifts over a long period of time
- excellent anti-rust properties
- low foaming tendency

Specification / Recommendations:

GM DEXRON II / II-C / II-D / II-E / III-G / III-H / B / III-F
ATF 3100 PL085, 3403-M115, ETL-7045 E, K17, LA 2634, N402
BMW ATF 4
BMW ETL 7045 / 7045E / 8072B, N402, LA 2634, LT 71141
BMW/Mini P/N 81 22 9 400 272/275
BMW/Mini P/N 83 22 0 026 922 (BMW 7045 E)
BMW/Mini P/N 83 22 0 403 248/249
BMW/Mini P/N 83 22 9 407 765 (BMW LA 2634),
Bosch TE-ML 09
Daimler Mercedes DTFR 13C100 (MB 236.1)
DTFR 13C140 (236.7), DTFR 13C150 (236.8), DTFR 13C117 (236.9)
DTFR 13C180 (236.91)
Fiat Chrysler ASRC, ATF+, ATF+2, ATF+3, ATF +4,
Fiat P/N 68333587AA, SP-III, Type 7176E, Type 9602
WSS-M2C919-E (Mercon V), WSS-M2C922-A1,
FORD/Lincoln/Mercury P/N XT-2-QDX [M], P/N XT-2-QSM [Syn]
P/N XT-8-QAW [Premium], P/N XT-9-QMM5 [FNR5]
GM/GMC/Opel/Saturn ATF Z1, P/N 22717466
P/N 88900925/9986195, P/N 9985010, T-IV, Type A Suffix A
Genuine ATF, JWS 3314, JWS-3309 T4, P/N 00232-19023,
Honda/Acura Z-1 (P/N 08200-9001 & 08200-9001A), ATF DPSF-II
Isuzu P/N 08200-9001, Isuzu ATF II/III, Genuine ATF
Jaguar JLM 20238 / 20292 / 21044 / K17, WSS-M2C922-A1, LT 71141
Land Rover Texaco ETL-7045E, ATF N402, JWS3309US
Mazda ATF M-5, N-1, S-1, F-1, M3, JWS 3317, M-5,
Mitsubishi ATF-J2, Dia Queen AW, DII/ DIII, SP
Mercedes A 0019892203, ATF 3403 -M115
Porsche P/N 000 043 204 41, P/N 000 043 204 63
Porsche P/N 000 043 205 28, P/N 999 917 547 00 (A2), LT 71141
Allison C-2, C-3, C-4, TES-295, TES-389
Aisin Warner JWS 3309
BMW P/N 83 22 2 220 438/440/442
BMW/Mini P/N 83 22 0 024 249/359
BMW/Mini P/N 81 22 9 407 858/859
BMW/Mini P/N 83 22 0 402 413
BMW/Mini P/N 83 22 7 542 290,
BMW/Mini P/N 83 22 9 407 807 (LT 71141)
Daihatsu D3-SP
DTFR 13C120 (236.2), 236.5, 236.6
MB 236.10, 236.11, 236.12, 236.14
FIAT 9.55550-AV1 / -AV4
MB 236.10/12, P/N 05127382AA
Ford ESP-M2C138-CJ, ESP-M2C166-H
XT-5-QMC (Mercon V), XT-5-QSM (V Syn)
P/N XT-5-QM or -DM [V]
Mobil ATF 3309
P/N 19 40 700/767, P/N 21005966 (transaxle)
Hyundai/Kia ATF Red-1K, SP / SP-II / III,
P/N 04500-00140, P/N U M040 CH-020 Red-1
Idemitsu ATF HP, K17
Jaso M315, Class 1A, 1A-02
MAN 339 A, D, F
Mazda P/N XT-9-QMM5, M-III, Type T-IV
Mitsubishi P/N MS991156, SP-II / III,
Nissan/Infinity 402, Fluid A, Matic-D / J / K / W
Porsche P/N 000 043 205 09
Peugeot P/N Z 000169756

Made in Germany

Specification / Recommendations:

PSA AL4 / 4HP20, P/N 9730AE, B71 2340, P/N Z 000169756
Rolls Royce Oil No. PL 31493PA
Saab ATF HP, P/N 93 160 393, 3309 - T-IV
Shell 3403-M115, LA 2634
Suzuki 2326/ 2384K/ 3314/ 3317/ 5D06, Matic D/J
Toyota/Lexus/Scion Type D-II/T/T-II/T-III/T-IV, JWS 3309, 3324
VW/Audi G 052 162 (A1, A2), G 052 990 (A2)
Voith H55.6335.XX, Svc Bltn # 013 / 118
Volvo P/N 1161521/ 1161621, 1161540 / 1161640
ZF TE-ML 05L / 11A / 11B / 21L
Renault DP-0, Matic D2, SATF-D
Renk Genuine Oil
Saturn Dex- IIIG, T-IV Fluid, P/N 22689186
SSANG YONG DSIH 5M-52, 5M-66
Subaru HP, P/N K0140Y0700
VW/Audi LT 71141, G 052 025 A2, G 052 055,
VW/Audi G 055 025 (A2), US 000 162
Volvo 1273,41, CE 97340, 97341
ZF 6 Speed (S671 090 255)
ZF LifeguardFluid 5 (ZF No. S671 090 170)

Typical values:

ATF Multi Vehicle	Unit	Value	Method
Density at 15°C	kg/m³	850	DIN 51 757
Color		rot	Visuell
Viscosity at 40°C	mm²/s	38,2	DIN 51 562
Viskosität bei 100°C	mm²/s	7,0	DIN 51 562
Viscosity index		150	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	228	DIN IS0 2592

Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded. Further information is available on the safety data sheet.

Hengst SE
Nienkamp 55-85
48147 Münster · Germany
Tel.: +49 251 20202-0

Made in Germany