



Safety Data Sheet

according to GHS

Date of issue: 23.01.2026

Version number 8.0

Revision: 01.11.2025

1 Identification of the substance or mixture and of the supplier

Other means of identification

Trade name: ATE Brake Cylinder Paste

Article number: 03.9902-05xx.x / 7000xx

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Technical preservative and anti-corrosion agent

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

AUMOVIO Aftermarket GmbH

Guerickestr. 7

60488 Frankfurt a. M.

Germany

Tel: +49-69-76031

Further information obtainable from:

Hazardous Substances Management Aftermarket, Central Materials Laboratory

ate.sicherheit@aumovio.com

Emergency telephone number:

INFOTRAC

+1-352-323-3500 (International)

2 Hazards identification

Classification of the substance or mixture

Aquatic Acute 2 H401 Toxic to aquatic life.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Label elements

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS09

Signal word

Void

Hazard statements

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P273 Avoid release to the environment.

P391 Collect spillage.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable

vPvB: Not applicable



Safety Data Sheet

according to GHS

Date of issue: 23.01.2026

Version number 8.0

Revision: 01.11.2025

Trade name: ATE Brake Cylinder Paste

(Contd. of page 1)

3 Composition/Information on ingredients

Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

5892-47-7	2,4,6-Tri-sec-butylphenol Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1); Skin Irrit. 2, H315	<10%
15520-05-5	2,2'-(Octylimino)bisethanol Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Acute Tox. 5, H313; Aquatic Chronic 3, H412	<3%
85507-95-5	9-Oxadeceonic acid (Z)-compd.with N-coco alkyl-1,1'-iminobis(2-propanol) Aquatic Acute 1, H400 (M=1); Skin Irrit. 2, H315; Aquatic Chronic 3, H412	<1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

Description of first aid measures

General information: Remove contaminated clothes and shoes immediately.

After inhalation: Supply fresh air and to be sure call for a doctor.

After skin contact:

Treat affected skin with cotton wool or cellulose. Then wash and rinse thoroughly with water and a mild cleaning agent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Call a doctor immediately.

Information for doctor:

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

Extinguishing media

Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture

May be released in case of fire: CO, CO₂, NO_x

Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)



Safety Data Sheet

according to GHS

Date of issue: 23.01.2026

Version number 8.0

Revision: 01.11.2025

Trade name: ATE Brake Cylinder Paste

(Contd. of page 2)

Environmental precautions:

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling Open and handle receptacle with care.

Information about fire - and explosion protection: Temperature class: T2

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store cool and dry.

Information about storage in one common storage facility:

Store away from flammable substances.

Store away from foodstuffs.

Further information about storage conditions:

This product is hygroscopic.

Store in dry conditions.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Appropriate engineering controls No further data; see section 7.

Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Use skin protection cream for skin protection.

Respiratory protection: Not necessary if room is well-ventilated.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

Butyl caoutchouc (butyl rubber): minimum breakthrough time 480 min; minimum layer thickness: 0.7 mm

(Contd. on page 4)

Date of issue: 23.01.2026

Version number 8.0

Revision: 01.11.2025

Trade name: ATE Brake Cylinder Paste

(Contd. of page 3)

NBR (nitrile rubber): minimum breakthrough time 30 min; minimum layer thickness: 0.4 mm

Eye protection: Safety glasses

Limitation and supervision of exposure into the environment

See section 6 and 7. No additional measures necessary.

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form:	Pasty
Colour:	Whitish
Odour:	Characteristic
Odour threshold:	Not determined

pH-value at 20 °C: 8.5

Change in condition

Melting point/freezing point:	Undetermined
Initial boiling point and boiling range:	>300 °C (FMVSS 116)

Flash point: >145 °C (DIN EN 22719 / ISO 2719)

Flammability: Not determined

Auto-ignition temperature: >300 °C (DIN 51794)

Decomposition temperature: Not determined

Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Explosion limits:

Lower:	Not determined.
Upper:	Not determined

Vapour pressure at 20 °C: <0.1 hPa

Density at 20 °C:	1 g/cm ³
Relative density	Not determined
Vapour density	Not applicable
Evaporation rate	Not applicable.
water:	Insoluble.

Partition coefficient: n-octanol/water: Not determined

Viscosity:

Dynamic:	Not applicable
Kinematic:	Not applicable

Other information

Particle characteristics	No further relevant information available.
Physical state	Not determined
	Solid

10 Stability and reactivity

Reactivity No further relevant information available.

(Contd. on page 5)



Safety Data Sheet

according to GHS

Date of issue: 23.01.2026

Version number 8.0

Revision: 01.11.2025

Trade name: ATE Brake Cylinder Paste

(Contd. of page 4)

Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

11 Toxicological information

Information on toxicological effects

Acute toxicity

LD/LC50 values relevant for classification:

The ATE values (all routes of exposure) exceeding the upper limits of classification to Category 5

ATE (Acute Toxicity Estimates)

Oral	LD50	>5.000 mg/kg (Calculation method)
Dermal	LD50	>5.000 mg/kg (Calculation method)

5892-47-7 2,4,6-Tri-sec-butylphenol

Oral	LD50	>2,000 mg/kg (rat)
------	------	--------------------

15520-05-5 2,2'-(Octylimino)bisethanol

Oral	LD50	1,157 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

Primary irritant effect:

Skin corrosion/irritation No classification is proposed, based on conclusive negative data.

Serious eye damage/irritation No classification is proposed, based on conclusive negative data.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Additional toxicological information:

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction) None.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

Toxicity

Aquatic toxicity:

5892-47-7 2,4,6-Tri-sec-butylphenol

EC50	0.675 mg/l (daphnia) (OECD 202 48 h)
LC50 (static)	2.2-5 mg/L (fish) (OECD 203 96 h)
NOEC	0.0675 mg/L (algae)
ErC50 (static)	0.391 mg/L (algae) (OECD 201 72 h)
ErC10 (static)	0.258 mg/L (algae) (OECD 201 72 h)

(Contd. on page 6)

EN-UN



Safety Data Sheet

according to GHS

Date of issue: 23.01.2026

Version number 8.0

Revision: 01.11.2025

Trade name: ATE Brake Cylinder Paste

(Contd. of page 5)

15520-05-5 2,2'-(Octylimino)bisethanol

EC50 (static)	1.35 mg/l (algae) (OECD 201 72 h)
	>100 mg/l (bacteria) (OECD 209)
	19.1 mg/l (daphnia) (OECD 202 48 h)
LC50	22 mg/L (fish) (OECD 203 96 h)
ErC10 (static)	0.402 mg/L (algae) (OECD 201 72 h)

Persistence and degradability

This product is, corresponding to the desired stability, heavily biodegradable.

Behaviour in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:
General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

PBT: Not applicable

vPvB: Not applicable

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Disposal should be based on the relevant state and local laws and regulations, the disposal process should avoid pollution of the environment.

Recommendation

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

Uncleaned packaging:
Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14 Transport information

UN-Number ADR, IMDG, IATA	UN3077
UN proper shipping name ADR	3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,4,6-Tri-sec-butylphenol)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,4,6-Tri-sec-butylphenol), MARINE POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (containing 2,4,6-Tri-sec-butylphenol)

(Contd. on page 7)

EN-UN



Safety Data Sheet

according to GHS

Date of issue: 23.01.2026

Version number 8.0

Revision: 01.11.2025

Trade name: ATE Brake Cylinder Paste

(Contd. of page 6)

Transport hazard class(es)

ADR, IMDG, IATA



Class Label 9 Miscellaneous dangerous substances and articles.
9

Packing group
ADR, IMDG, IATA III

Environmental hazards: Product contains environmentally hazardous substances:
2,4,6-Tri-sec-butylphenol
Marine pollutant: Symbol (fish and tree)
Special marking (ADR): Symbol (fish and tree)
Special marking (IATA): Symbol (fish and tree)

Special precautions for user Warning: Miscellaneous dangerous substances and articles.
Danger code: 90
EMS Number: F-A,S-F
Stowage Category A
Stowage Code SW23 When transported in BK3 bulk container, see 7.6.2.12 and 7.7.3.9.

Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable

Transport/Additional information:

ADR
Limited quantities (LQ) 5 kg
Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 g
Maximum net quantity per outer packaging: 1000 g
Transport category 3
Tunnel restriction code (-)
Remarks: Emergency Telephone (24/7)
INFOTRAC ID 116235
+1-352-323-3500 (International)
+1-800-535-5053 (North America)
Special Provision 375

IMDG
Limited quantities (LQ) 5 kg
Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 g
Maximum net quantity per outer packaging: 1000 g
Remarks: Emergency Telephone (24/7)
INFOTRAC ID 116235
+1-352-323-3500 (International)
+1-800-535-5053 (North America)
Special Provision 2.10.2.7

(Contd. on page 8)



Safety Data Sheet

according to GHS

Date of issue: 23.01.2026

Version number 8.0

Revision: 01.11.2025

Trade name: ATE Brake Cylinder Paste

(Contd. of page 7)

IATA
Remarks:

Emergency Telephone (24/7)
 INFOTRAC ID 116235
 +1-352-323-3500 (International)
 +1-800-535-5053 (North America)
 Special Provision A197

UN "Model Regulation":

UN 3077 ENVIRONMENTALLY HAZARDOUS
 SUBSTANCE, SOLID, N.O.S. (2,4,6-TRI-SEC-
 BUTYLPHENOL), 9, III

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. It is the sole responsibility of the importer or distributor to identify and comply with all legal requirements necessary for the lawful placing of chemical products on the market in the respective target countries.

Relevant phrases

H302 Harmful if swallowed.
 H313 May be harmful in contact with skin.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Recommended restriction of use For industrial or professional purposes only.

Department issuing SDS:

Hazardous Substances Management Aftermarket
 ate.sicherheit@aumovio.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 5: Acute toxicity – Category 5
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

(Contd. on page 9)



Safety Data Sheet according to GHS

Date of issue: 23.01.2026

Version number 8.0

Revision: 01.11.2025

Trade name: ATE Brake Cylinder Paste

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. of page 8)

*** Data compared to the previous version altered.**

-EN-UN-