



Safety Data Sheet

according to UN-GHS

Date of issue: 27.11.2025

Version number 6.0

Revision: 01.11.2025

1 Identification of the substance or mixture and of the supplier

Other means of identification

Trade name: Original ATE Brake Fluid SL.6 (DOT 4)

Article number: 03.9901-64xx.x / 7064xx

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture hydraulic liquid

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

AUMOVIO Aftermarket GmbH

Guerickestr. 7

60488 Frankfurt a. M.

Germany

Tel: +49-69-76031

Further information obtainable from:

Hazardous Substances Management Aftermarket, Central Materials Laboratory

ate.sicherheit@aumovio.com

Emergency telephone number:

INFOTRAC

+1-352-323-3500 (International)

2 Hazards identification

Classification of the substance or mixture

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

Label elements

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS08

Signal word Warning

Hazard-determining components of labelling:

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Hazard statements

H361 Suspected of damaging fertility or the unborn child.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

EN-UN



Safety Data Sheet

according to UN-GHS

Date of issue: 27.11.2025

Version number 6.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL.6 (DOT 4)

(Contd. of page 1)

Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

3 Composition/Information on ingredients

Chemical characterisation: Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

30989-05-0	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate Repr. 2, H361	≥30-<50%
	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Eye Dam. 1, H318; Acute Tox. 5, H313 Specific concentration limits: Eye Dam. 1; H318: C ≥ 30 % Eye Irrit. 2; H319: 20 % ≤ C < 30 %	≥3-<5%
110-97-4	1,1'-Iminodipropan-2-ol Eye Irrit. 2, H319	≥1-<2.5%
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol Eye Dam. 1, H318; Acute Tox. 5, H313 Specific concentration limits: Eye Dam. 1; H318: C ≥ 30 % Eye Irrit. 2; H319: 20 % ≤ C < 30 %	≥1-<2.5%

Additional information:

The content of CAS No 143-22-6 is a component of Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy) ethanol and 3,6,9,12-tetraoxahexadecan-1-ol.

For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

Description of first aid measures**General information:**

Take affected persons out of danger area.

Do not leave affected persons unattended.

Remove contaminated clothes and shoes immediately.

After inhalation:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Seek medical treatment.

After skin contact:

If skin irritation occurs: Get medical advice/attention.

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Protect unharmed eye.

After swallowing:

Do NOT induce vomiting.

Rinse mouth thoroughly with water.

Call a doctor immediately.

(Contd. on page 3)

EN-UN



Safety Data Sheet

according to UN-GHS

Date of issue: 27.11.2025

Version number 6.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL.6 (DOT 4)

(Contd. of page 2)

Information for doctor:

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

Extinguishing media

Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Boron oxides

Carbon monoxide (CO)

Nitrogen oxides (NO_x)

During heating or in case of fire poisonous gases are produced.

Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Temperature class: T3

(Contd. on page 4)



Safety Data Sheet

according to UN-GHS

Date of issue: 27.11.2025

Version number 6.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL.6 (DOT 4)

(Contd. of page 3)

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Storage at room temperature.

Information about storage in one common storage facility:

Store away from flammable substances.

Store away from foodstuffs.

Further information about storage conditions:

This product is hygroscopic.

Store in dry conditions.

Keep container tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Appropriate engineering controls No further data; see section 7.

Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

Use skin protection cream for skin protection.

Respiratory protection:

In the case of vapour formation use a respirator with an approved filter.

Equipment should conform to EN 14387.

If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.

filter ABEK-P2

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

Butyl caoutchouc (butyl rubber): minimum breakthrough time 480 min; minimum layer thickness: 0.7 mm

NBR (nitrile rubber): minimum breakthrough time 30 min; minimum layer thickness: 0.4 mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses

Body protection: Protective work clothing

(Contd. on page 5)



Safety Data Sheet

according to UN-GHS

Date of issue: 27.11.2025

Version number 6.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL.6 (DOT 4)
Limitation and supervision of exposure into the environment

See section 6 and 7. No additional measures necessary.

(Contd. of page 4)

9 Physical and chemical properties

Information on basic physical and chemical properties
General Information
Appearance:

Form:	Fluid
Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value at 20 °C: 8 (50 %) (ASTM D 1287)

Change in condition

Melting point/freezing point:	<-70 °C (ASTM D 1177)
Initial boiling point and boiling range:	265 °C (ASTM D 1120)

Flash point: 136 °C (DIN EN 22719 / ISO 2719)

Flammability Not applicable.

Auto-ignition temperature: >300 °C (DIN 51794)

Decomposition temperature: 360 °C

Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

Vapour pressure at 20 °C: 0.27 Pa (Syracuse)

Density at 20 °C: 1.06 g/cm³ (DIN 51757)

Relative density Not determined.

Vapour density Not determined.

Evaporation rate Not determined.

water: Fully miscible.

Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Dynamic:	Not determined.
Kinematic at 20 °C:	12.3 mm ² /s (DIN 51562)

Other information No further relevant information available.

Particle characteristics Not applicable.

Physical state Liquid

10 Stability and reactivity

Reactivity No further relevant information available.

(Contd. on page 6)



Safety Data Sheet

according to UN-GHS

Date of issue: 27.11.2025

Version number 6.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL.6 (DOT 4)

(Contd. of page 5)

Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources.

Incompatible materials: No further relevant information available.

Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Boron oxides

Hydrocarbons

11 Toxicological information

Information on toxicological effects

Acute toxicity

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal	LD50	>5.000 mg/kg (Calculation method)
--------	------	-----------------------------------

30989-05-0 Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Oral	LD50	>2,000 mg/kg (rat) (OECD 401)
------	------	-------------------------------

Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
--------	------	-------------------------------

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>3,000 mg/kg (rabbit)
--------	------	-----------------------

110-97-4 1,1'-Iminodipropan-2-ol

Oral	LD50	>2,000 mg/kg (rat) (OECD 401)
------	------	-------------------------------

Dermal	LD50	>5,000 mg/kg (rabbit)
--------	------	-----------------------

143-22-6 2-[2-(2-butoxyethoxy)ethoxy]ethanol

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>2,000 mg/kg (rabbit)
--------	------	-----------------------

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Additional toxicological information:

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

EN-UN

(Contd. on page 7)



Safety Data Sheet

according to UN-GHS

Date of issue: 27.11.2025

Version number 6.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL.6 (DOT 4)

(Contd. of page 6)

12 Ecological information

Toxicity

Aquatic toxicity:

30989-05-0 Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

EC50	>100 mg/l (algae) (72 h)
	>100 mg/l (daphnia) (48 h)
LC50	>100 mg/L (fish) (96 h)

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

EC50	>100 mg/l (algae)
LC50	>100 mg/L (daphnia)
	>100 mg/L (fish) (DIN 38412 96 h)

110-97-4 1,1'-Iminodipropan-2-ol

EC50 (static)	>100 mg/l (algae) (72 h)
	>100 mg/l (daphnia) (92/69/EWG 48 h)
LC50 (static)	>100 mg/L (fish) (OECD 203 96 h)

143-22-6 2-[2-(2-butoxyethoxy)ethoxy]ethanol

EC50	>100 mg/l (algae)
LC50	>100 mg/L (daphnia)
	>100 mg/L (fish)

Persistence and degradability No further relevant information available.

Other information: The product is easily biodegradable.

Behaviour in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment Not applicable.

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Disposal should be based on the relevant state and local laws and regulations, the disposal process should avoid pollution of the environment.

Recommendation

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

Uncleaned packaging:

Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

EN-UN

(Contd. on page 8)



Safety Data Sheet

according to UN-GHS

Date of issue: 27.11.2025

Version number 6.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL.6 (DOT 4)

(Contd. of page 7)

14 Transport information

UN-Number ADR, ADN, IMDG, IATA	Void
UN proper shipping name ADR, ADN, IMDG, IATA	Void
Transport hazard class(es) ADR, ADN, IMDG, IATA Class	Void
Packing group ADR, IMDG, IATA	Void
Environmental hazards: Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
UN "Model Regulation":	Void

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

It is the sole responsibility of the importer or distributor to identify and comply with all legal requirements necessary for the lawful placing of chemical products on the market in the respective target countries.

Relevant phrases

H313 May be harmful in contact with skin.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

Recommended restriction of use For industrial or professional purposes only.

Department issuing SDS:

Hazardous Substances Management Aftermarket

ate.sicherheit@aumovio.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)



Safety Data Sheet

according to UN-GHS

Date of issue: 27.11.2025

Version number 6.0

Revision: 01.11.2025

Trade name: Original ATE Brake Fluid SL.6 (DOT 4)*(Contd. of page 8)*

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 5: Acute toxicity – Category 5

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

*** Data compared to the previous version altered.**

EN-UN