

Anziehvorschrift für Zylinderkopf		076.893 passend für / suitable for adaptable à / adaptable a Alfa / Fiat / Opel	 Das Original					
Tightening Instructions for Cylinder Head								
Instructions de serrage pour culasse								
Prescripciones de apriete para culatas								
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo		Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete						
 803.060 M 10x1,25x153								
<table><tr><td>Anziehen/ Tightening/ Serrage/ Apriete</td><td>* ➤ ➤ ➤ ➤</td><td>25 Nm 90° 90° 90° 45°</td></tr></table>				Anziehen/ Tightening/ Serrage/ Apriete	* ➤ ➤ ➤ ➤	25 Nm 90° 90° 90° 45°		
Anziehen/ Tightening/ Serrage/ Apriete	* ➤ ➤ ➤ ➤	25 Nm 90° 90° 90° 45°						
Zeichenerklärung / Explanations / Explication / Explicacion								
<table><tr><td>* ★ ☐ ● ➤</td><td>neue Zylinderkopf- schrauben verwenden Warmlauf (80°C) Schrauben einzeln lösen und wieder anziehen Setzzeit Drehwinkel</td><td>use new cylinder head bolts warm up time (80°C) loosen and tighten each bolt relaxation time torque angle</td><td>utiliser des vis neuves chauffage (80°C) deserrer et serrer vis par vis durée de tassement angle de serrage</td><td>emplar tornillos nuevos calentamiento (80°C) aflojar y apretar tornillo a tornillo tiempo de espera ángulo de giro</td></tr></table>				* ★ ☐ ● ➤	neue Zylinderkopf- schrauben verwenden Warmlauf (80°C) Schrauben einzeln lösen und wieder anziehen Setzzeit Drehwinkel	use new cylinder head bolts warm up time (80°C) loosen and tighten each bolt relaxation time torque angle	utiliser des vis neuves chauffage (80°C) deserrer et serrer vis par vis durée de tassement angle de serrage	emplar tornillos nuevos calentamiento (80°C) aflojar y apretar tornillo a tornillo tiempo de espera ángulo de giro
* ★ ☐ ● ➤	neue Zylinderkopf- schrauben verwenden Warmlauf (80°C) Schrauben einzeln lösen und wieder anziehen Setzzeit Drehwinkel	use new cylinder head bolts warm up time (80°C) loosen and tighten each bolt relaxation time torque angle	utiliser des vis neuves chauffage (80°C) deserrer et serrer vis par vis durée de tassement angle de serrage	emplar tornillos nuevos calentamiento (80°C) aflojar y apretar tornillo a tornillo tiempo de espera ángulo de giro				
Motortyp / Engine type / Type de moteur / Tipo de motor Ø: 81,7 mm; $\frac{1}{4}$: 0,65 mm Mot: A18XER, Z18XER, Z16LET, Z16XER, A16XER Z16LEL, A16LEL, Z16LER, A16LER, 939 A4.000 1.6 - 1.8 ltr 103-132 KW (140-192 PS) Astra H/J, Corsa D, Insignia, Meriva A, Signum, Vectra C, Zafira B, Alfa 159, Fiat Croma								
ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601		*076.893*						