


Anziehvorschrift für Zylinderkopf		535.740		 Das Original																				
Tightening Instructions for Cylinder Head		passend für / suitable for adaptable à / adaptable a																						
Instructions de serrage pour culasse																								
Prescripciones de apriete para culatas		Mercedes-Benz																						
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo		Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete																						
		<table border="1"><tr><td>9</td><td>5</td><td>1</td><td>4</td><td>8</td></tr><tr><td>10</td><td>6</td><td>2</td><td>3</td><td>7</td></tr><tr><td>10</td><td>6</td><td>2</td><td>3</td><td>7</td></tr><tr><td>9</td><td>5</td><td>1</td><td>4</td><td>8</td></tr></table>			9	5	1	4	8	10	6	2	3	7	10	6	2	3	7	9	5	1	4	8
9	5	1	4	8																				
10	6	2	3	7																				
10	6	2	3	7																				
9	5	1	4	8																				
535.860 M 11x1,5x170																								
Anziehen/ Tightening/ Serrage/ Apriete		M11 20 Nm 40 Nm 90° 90°		M8 15 Nm 90°																				
* ➤ ➤				➤																				
Zeichenerklärung / Explanations / Explication / Explicacion																								
* ★ ☐ ● ➤	neue Zylinderkopf-schrauben verwenden Warmlauf (80°C) Schrauben einzeln lösen und wieder anziehen Setzzeit Drehwinkel	use new cylinder head bolts warm up time (80°C) loosen and tighten each bolt relaxation time torque angle	utiliser des vis neuves chauffage (80°C) deserrer et serrer vis par vis durée de tassement angle de serrage	emplar tornillos nuevos calentamiento (80°C) aflojar y apretar tornillo a tornillo tiempo de espera ángulo de giro																				
Motortyp / Engine type / Type de moteur / Tipo de motor																								
Ø 98,7 mm, 1,1 mm																								
Mot: M 273.961,963,965																								
S500 (W221), CL500 (C216) GL500 (X164), SL500 (R230)																								
links/left/gauche/izquierda/sinistra																								
ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601			*535.740*																					