



<b>Anziehvorschrift für Zylinderkopf</b>	<b>715.210</b>	 Das Original
<b>Tightening Instructions for Cylinder Head</b>		
<b>Instructions de serrage pour culasse</b>		
<b>Prescripciones de apriete para culatas</b>		
	passend für / suitable for adaptable à / adaptable a	<b>Nissan</b>

Schraubenkopf / Head shape      Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete  
Tête de vis / Cabeza de tornillo



- |             |   |               |
|-------------|---|---------------|
| Anziehen/   | * | 39 Nm tighten |
| Tightening/ | ➤ | 180° tighten  |
| Serrage/    | ➤ | -360° loosen  |
| Apriete     |   | 39 Nm tighten |
|             | ➤ | 90° tighten   |
|             | ➤ | 90° tighten   |

Zeichenerklärung / Explanations / Explication / Explicacion

*	neue Zylinderkopfschrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos
★	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)
☐	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo
●	Setzzeit	relaxation time	durée de tassement	tiempo de espera
➤	Drehwinkel	torque angle	angle de serrage	ángulo de giro

**Motortyp / Engine type / Type de moteur / Tipo de motor**

Ø: 89 mm;  $\frac{1}{2}$ : 0,95 mm

Mot:                    YD25DDTi  
2,5 ltr.  
98-106 kW (133-144 PS)

Navara (D40) 2,5 dCi  
Pick up (D22) 2,5 Di

ElringKlinger AG, Max-Eyth-Str.2  
72581 Dettingen / Erms. Tel. 07123/724 601

**\*715.210\***