

# PROMOTIVE EFB









690500105K182



## Vehicles with high energy demands and basic hoteling functions.

The VARTA ProMotive EFB is engineered to exceed the rigorous demands of heavy commercial vehicles. Built to deliver exceptional power and reliability, it's the ideal choice for vehicles with high energy requirements, including those equipped with basic overnight hoteling

### VEHICLE KEY BENEFITS

|  |                                      |  |
|--|--------------------------------------|--|
|  | <b>3x cycle life</b>                 | 3x cycle life compared with a conventional battery.  |
|  | <b>High energy demands</b>           | Engineered to meet the most demanding energy requirements.   |
|  | <b>Basic Hoteling</b>                | For basic energy demands, i.e. parking coolers/heaters, up to three nights/week.                           |
|  | <b>High vibration resistance</b>     | Built to withstand extreme road conditions and fitment at the end of frame with high vibration resistance. |
|  | <b>End of frame installation</b>     | Suitable for end of frame installation.  |
|  | <b>Original equipment spare part</b> | Meets all OE criteria from the vehicle manufacturer.   |
|  | <b>Engineered in Germany</b>         | Engineered with precision and expertise in Germany.  |
|  | <b>Made in Europe</b>                | Produced to the highest European standards ensuring best in class manufacturing quality.                   |

# PROMOTIVE EFB

690500105K182

## TECHNICAL DATA

|                |                 |                     |                    |
|----------------|-----------------|---------------------|--------------------|
| Capacity:      | <b>190 Ah</b>   | CCA:                | <b>1050 A</b>      |
| Voltage:       | <b>12 V</b>     | Dimensions (L/W/H): | <b>513/223/223</b> |
| Case Size:     | <b>B</b>        | Short Code:         | <b>B90</b>         |
| UK-Code:       | <b>629EFB</b>   | ETN:                | <b>690500105</b>   |
| Weight filled: | <b>47,21 kg</b> | Base Hold-down:     | <b>B00</b>         |

## DRAWINGS

