



# HEATER HOSE CONNECTORS

Product type 7315



Gates heater hose connectors are recommended for small diameter heater and radiator hoses to provide a better seal between hoses with either the same or different inside diameters. Using straight, reducer, elbow and "T" connectors, almost any hose configuration can be constructed. They can be used on both light-duty and heavy-duty applications.

- Made of 100% glass-reinforced nylon
- Resistant to coolant additives, petrol, diesel, oil and LPG
- Anti-rotation device prevents the hose from twisting off the fitting
- Single-barb design ensures a leak-proof seal
- Superior resistance to extreme temperatures from -65°C to +250°C
- Maximum working pressure up to 2 MPa (20 kg/cm<sup>2</sup>)

**Packaging:**

- Outside diameter up to 19 mm: 5 pieces in a plastic bag
- Outside diameter of 25 mm: 2 pieces in a plastic bag

Heater hose connectors			
PN			
		mm	"
7315-00913*	28601	6	1/4
7315-00103	28600	8	5/16
7315-00914*	28602	10	3/8
7315-00915*	28603	12	1/2
7315-00916*	28604	15	5/8
7315-00917*	28605	19	3/4
7315-00918	28606	25	1
7315-00908*	28621	6	1/4
7315-00102	28620	8	5/16
7315-00909*	28622	10	3/8
7315-00910*	28623	12	1/2
7315-00911*	28624	15	5/8
7315-00912*	28625	19	3/4
7315-00919	28626	25	1
7315-00931*	28631	6	1/4
7315-00101	28630	8	5/16
7315-00932*	28632	10	3/8
7315-00933*	28633	12	1/2
7315-00934*	28634	15	5/8
7315-00935*	28635	19	3/4
7315-00936	28636	15 x 10	5/8 x 3/8
7315-00937	28637	19 x 10	3/4 x 3/8
7315-00938	28638	25	1

Reducer connectors			
PN			
		mm	"
7315-00104	28594	10 → 8	3/8 → 5/16
7315-00921*	28609	12 → 10	1/2 → 3/8
7315-00922*	28610	15 → 12	5/8 → 1/2
7315-00923*	28611	19 → 15	3/4 → 5/8
7315-00924	28612	25 → 19	1 → 3/4
* Included in heater hose connector kit			



# CONNECTORS FOR FUEL LINE, WINDSHIELD WASHER HOSE AND VACUUM TUBING



Product type 7315



Gates connectors are recommended for small-diameter hoses to provide a better seal between hoses with either the same or different inside diameters. Using straight, elbow, reducer, "T" and "Y" shapes, almost any hose configuration can be constructed.

- Unique single-barb design ensures a leak-proof seal
- Resistant to coolant additives, petrol, diesel, oil and LPG
- For hoses with ID of 2 mm to 12 mm
- Glass-reinforced nylon resists extreme temperatures from -65°C to +250°C
- Working pressure up to 2 MPa (20 kg/cm<sup>2</sup>)

**Packaging:**  
5 pieces in a plastic bag.

FUEL HOSE CONNECTORS			
PN			
		mm	"
7315-00861*	28561	2	3/32
7315-00862*	28562	3	1/8
7315-00863*	28563	4	5/32
7315-00864*	28564	5	3/16
7315-00913	28601	6	1/4
7315-00103	28600	8	5/16
7315-00914	28602	10	3/8
7315-00915	28603	12	1/2

7315-00872*	28572	3	1/8
7315-00873*	28573	4	5/32
7315-00874*	28574	5	3/16
7315-00908	28621	6	1/4
7315-00102	28620	8	5/16
7315-00909	28622	10	3/8
7315-00910	28623	12	1/2

FUEL HOSE CONNECTORS			
PN			
		mm	"
7315-00881*	28581	2	3/32
7315-00882*	28582	3	1/8
7315-00883*	28583	4	5/32
7315-00884*	28584	5	3/16
7315-00931	28631	6	1/4
7315-00101	28630	8	5/16
7315-00932	28632	10	3/8
7315-00933	28633	12	1/2

7315-00852*	28552	3	1/8
7315-00854*	28554	5	3/16

REDUCER CONNECTORS			
PN			
		mm	"
7315-00892*	28592	4 → 3	5/32 → 1/8
7315-00893*	28593	6 → 5	1/4 → 3/16
7315-00104	28594	10 → 8	3/8 → 5/16
7315-00921	28609	12 → 10	1/2 → 3/8

\* Included in fuel line and vacuum tubing connector kit