

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0

Page 1 / 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Engine Oil SAE 0W-30 Longlife Plus
Article number: 33 11 1679, 33 11 1869, 33 11 1872, 33 11 1873, 33 11 1874, 33 11 1875

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Engine oil

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company SWAG Autoteile GmbH
Am Kiesberg 4-6
42117 Wuppertal / GERMANY
Phone +49 (0)202 26454-0
Fax +49 (0)202 26454-5000
Homepage www.swag.de
E-mail info@swag.de

Address enquiries to

Technical information info@swag.de

Safety Data Sheet info@swag.de

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

No classification.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms none

Signal word none

Hazard statements none

Precautionary statements none

Special labelling EUH210 Safety data sheet available on request.

Contains: C14-16-18 Alkyl phenol. EUH208 May produce an allergic reaction.

2.3 Other hazards

Environmental hazards Does not contain any PBT or vPvB substances.
Contains no ingredients with endocrine-disrupting properties.

Other hazards No particular hazards known.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0 Page 2 / 16

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
20 - < 50	1-Decene, homopolymer, hydrogenated
	CAS: 68037-01-4, EINECS/ELINCS: 500-183-1, Reg-No.: 01-2119486452-34-XXXX
	GHS/CLP: Asp. Tox. 1: H304
20 - < 50	Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 10	Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-56-9, EINECS/ELINCS: 265-159-2, EU-INDEX: 649-469-00-9, Reg-No.: 01-2119480132-48-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 10	Paraffin oils (petroleum), catalytic dewaxed heavy
	CAS: 64742-70-7, EINECS/ELINCS: 265-174-4, EU-INDEX: 649-477-00-2, Reg-No.: 01-2119487080-42-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 10	Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt)
	CAS: 64742-65-0, EINECS/ELINCS: 265-169-7, Reg-No.: 01-2119471299-27-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 10	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract)
	CAS: 72623-86-0, EINECS/ELINCS: 276-737-9, EU-INDEX: 649-221-00-X, Reg-No.: 01-2119474878-16-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 10	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based
	CAS: 72623-87-1, EINECS/ELINCS: 276-738-4, EU-INDEX: 649-483-00-5, Reg-No.: 01-2119474889-13-XXXX
	GHS/CLP: Asp. Tox. 1: H304
0,1 - <1	C14-16-18 Alkyl phenol
	CAS: 1190625-94-5, EINECS/ELINCS: 931-468-2, Reg-No.: 01-2119498288-19-XXXX
	GHS/CLP: Skin Sens. 1B: H317 - STOT RE 2: H373

Comment on component parts

For full text of H-statements: see SECTION 16.
Contains less than 3% w/w DMSO-extract (only for mineral oils)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information	Take off contaminated clothing and wash before reuse.
Inhalation	Ensure supply of fresh air. In the event of symptoms seek medical treatment.
Skin contact	When in contact with the skin, clean with soap and water. Consult a doctor if skin irritation persists.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Do not induce vomiting. Seek medical advice immediately. Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Headache

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Forward this sheet to your doctor.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0

Page 3 / 16

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Foam, dry powder, water spray jet, carbon dioxide.

Extinguishing media that must not be used Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Some risk of slipping due to spillage of product.
Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.
Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. oil binder).
Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosols.
Use only in well-ventilated areas.

The product is combustible.

Do not eat, drink or smoke when using this product.
After worktime and before work breaks the affected skin areas must be thoroughly cleaned.
Use barrier skin cream.
Take off contaminated clothing and wash before reuse.
Contaminated work clothing should not be allowed out of the workplace.
Cloths contaminated with product should not be kept in trouser pockets.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.

Do not store together with food and animal food/diet.

Keep container in a well-ventilated place.
Keep container tightly closed.

7.3 Specific end use(s)

See product use, SECTION 1.2

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0

Page 4 / 16

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (UK)

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
Long-term exposure: 5 mg/m ³ , oil mist
Short-term exposure (15-minute): 10 mg/m ³
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract)
CAS: 64742-56-9, EINECS/ELINCS: 265-159-2, EU-INDEX: 649-469-00-9, Reg-No.: 01-2119480132-48-XXXX
Long-term exposure: 1200 mg/m ³

Ingredients with occupational exposure limits to be monitored EU (2004/37/EG)

not relevant

DNEL

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5.58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, inhalative, Long-term - local effects, 1.19 mg/m ³
general population, oral, Long-term - systemic effects, 740 µg/kg bw/day
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5.58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 0.97 mg/kg bw/day
general population, oral, Long-term - systemic effects, 0.74 mg/kg bw/day
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5.58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, oral, Long-term - local effects, 740 µg/kg bw/day
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5.58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, inhalative, Long-term - local effects, 1.19 mg/m ³
general population, oral, Long-term - systemic effects, 740 µg/kg bw/day
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5.58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, inhalative, Long-term - local effects, 1.19 mg/m ³
general population, inhalative, Long-term - systemic effects, 740 µg/kg bw/day
1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0

Page 5 / 16

PNEC

There are no DNEL values established for the substance.
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
Industrial, inhalative, Long-term - systemic effects, 1,17 mg/m ³
Industrial, dermal, Long-term - systemic effects, 300 µg/kg bw/d
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m ³
Industrial, inhalative, Long-term - local effects, 5.58 mg/m ³
Industrial, dermal, Long-term - systemic effects, 970 µg/kg bw/day
general population, inhalative, Long-term - local effects, 1.19 mg/m ³
general population, oral, Long-term - systemic effects, 740 µg/kg bw/day

Substance
Distillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
oral (food), 9,33 mg/kg
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
oral (food), 9,33 mg/kg food
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
oral (food), 9,33 mg/kg food
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
oral (food), 9.33 mg/kg food
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
oral (food), 9.33 mg/kg food
1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4
There are no PNEC values established for the substance.
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
freshwater, 100 µg/l
seawater, 10 µg/l
sewage treatment plants (STP), 100 mg/l
sediment (freshwater), 4266,16 mg/kg dw
sediment (seawater), 426,62 mg/kg dw
soil, 852,58 mg/kg dw
oral (food), 3,3 mg/kg
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
oral (food), 9.33 mg/kg food

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0

Page 6 / 16

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. General exposure limit for oil mist should be noted. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. In full contact: > 0,4 mm: Nitrile rubber, >120 min (EN 374-1/-2/-3).
Skin protection	light protective clothing
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.
Respiratory protection	No special measures necessary.
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	liquid
Color	amber colour
Odor	characteristic
Odour threshold	No information available.
pH-value	not applicable
pH-value [1%]	No information available.
Boiling point or initial boiling point and boiling range [°C]	not applicable
Flash point [°C]	238(EN ISO 2592)
Flammability	No information available.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	No information available.
Density [g/cm³]	0,84 15°C (DIN 51757)
Relative density	not determined
Bulk density [kg/m³]	not applicable
Solubility in water	immiscible
Solubility other solvents	No information available.
Partition coefficient n-octanol/water (log value)	No information available.
Kinematic viscosity	61,8 mm²/s (40°C) (DIN 53211/4)
Relative vapour density	No information available.
Melting point [°C]	No information available.
Auto-ignition temperature [°C]	not applicable
Decomposition temperature [°C]	No information available.
Particle characteristics	No information available.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0

Page 7 / 16

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

No hazardous reactions known.

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

Oxidizing agent
Strong basic compounds
Strong acids.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0

Page 8 / 16

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Product
oral, Based on the available information, the classification criteria are not fulfilled.
Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
LD50, oral, Rat, 5000 mg/kg bw
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
LD50, oral, Rat, >5000 mg/kg bw (OECD 401)
NOAEL, oral, Rat, >1000 mg/kg bw (OECD 421)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LD50, oral, Rat, 5000 mg/kg bw
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
LD50, oral, Rat, 5000 mg/kg bw
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LD50, oral, Rat, 5000 mg/kg bw
1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4
LD50, oral, Rat, 2000 - 5000 mg/kg bw
NOAEL, oral, Rat, 1000 - 6771 mg/kg bw/day
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
LD50, oral, Rat, >2000 mg/kg bw
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
LD50, oral, Rat, >5000 mg/kg bw
LOAEL, oral, Rat, 125 mg/kg bw/day

Acute dermal toxicity

Product
dermal, Based on the available information, the classification criteria are not fulfilled.
Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
LD50, dermal, Rabbit, 2000 - 5 00 mg/kg bw
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
LD50, dermal, Rabbit, >5000 mg/kg bw (OECD 403)
NOAEL, dermal, Rat, >2000 mg/kg bw (OECD 414)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LD50, dermal, Rabbit, > 2000 - 5000 mg/kg bw
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
LD50, dermal, Rabbit, 2000 - 5000 mg/kg bw
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LD50, dermal, Rabbit, 2000 - 5000 mg/kg bw
1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4
LD50, dermal, Rat, 2000 mg/kg bw
C14-16-18 Alkyl phenol, CAS: 1190625-94-5

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0

Page 9 / 16

LD50, dermal, Rat, >2000 mg/kg bw
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
LD10, dermal, Rabbit, >2000 mg/kg bw
NOAEL, dermal, Rabbit, >1000 mg/kg bw/day

Acute inhalational toxicity

Product
inhalative, Based on the available information, the classification criteria are not fulfilled.
Substance
Distillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
LC50, inhalative, Rat, >5,53 mg/l air (OECD 403)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
LC50, inhalative, Rat, 2,18 - 5,53 mg/L air 4h, 4h
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h
1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4
LC50, inhalative, Rat, 900 - 5200 mg/m³ air
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
LC50, inhalative, Rat, 18 - 5.53 mg/L air, 4h
NOAEC, inhalative, Rat, 980 mg/m³ air

Serious eye damage/irritation Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
Eye, non-irritating
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
Eye, non-irritating
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
Eye, non-irritating

Skin corrosion/irritation Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
dermal, non-irritating
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
dermal, non-irritating
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
dermal, non-irritating

Respiratory or skin sensitisation Based on the available information, the classification criteria are not fulfilled.
May produce an allergic reaction.
Calculation method

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0 Page 10 / 16

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
dermal, non-sensitizing
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
dermal, non-sensitizing
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
dermal, non-sensitizing

Specific target organ toxicity — single exposure Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity — repeated exposure Based on the available information, the classification criteria are not fulfilled.

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day
NOAEL, dermal, Rabbit, 1000 mg/kg bw/day
NOAEC, inhalative, Rat, 980 mg/m³ air
LOAEL, oral, Rat, 125 mg/kg bw/day
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
NOAEC, inhalative, Rat, 980 mg/m³, no adverse effect observed
LOAEL, oral, Rat, 125 mg/kg bw/day, adverse effect observed
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOAEL, inhalative, Rat, 980 mg/m³ air, no adverse effect observed
LOAEL, dermal, mouse, 100 mg/kg bw/day, The effects observed are not sufficient for classification.
LOAEL, oral, Rat, 125 mg/kg bw/day, The effects observed are not sufficient for classification.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day
NOAEC, inhalative, Rat, 980 mg/m³ air
LOAEL, oral, Rat, 125 mg/kg bw/day
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day
NOAEC, inhalative, Rat, 980 mg/m³ air
LOAEL, oral, Rat, 125 mg/kg bw/day

Mutagenicity Based on the available information, the classification criteria are not fulfilled.

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
in vitro, negativ
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
in vitro, negativ
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
in vitro, negativ

Reproduction toxicity Based on the available information, the classification criteria are not fulfilled.

- Fertility

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7



SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0 Page 11 / 16

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
NOAEL, oral, Rat, 1000 mg/kg bw/day, In vivo study, negativ
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOAEL, oral, Rat, 1000 mg/kg bw/d, no adverse effect observed
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
NOAEL, oral, Rat, 1000 mg/kg bw/day

- Development

Substance
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
NOAEL, oral, Rat, 1000 mg/kg bw/day, In vivo study, negativ

Carcinogenicity	Based on the available information, the classification criteria are not fulfilled.
Aspiration hazard	Based on the available information, the classification criteria are not fulfilled.
General remarks	Toxicological data of complete product are not available. The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties	Contains no ingredients with endocrine-disrupting properties.
11.2.2 Other information	none

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0

Page 12 / 16

SECTION 12: Ecological information

12.1 Toxicity

Product
Based on the available information, the classification criteria are not fulfilled.
Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
EL50, (48h), Invertebrates, 10 g/L
NOELR, (14d), Fish, 1 mg/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), Fish, 100 mg/L
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9
EL50, (24h), Daphnia magna, >10000 mg/l (OECD 202)
LL50, (96h), Pimephales promelas, >100 mg/l (OECD 203)
NOEL, (21d), Daphnia magna, 10 mg/l (OECD 211)
NOEL, (72h), Pseudokirchneriella subcapitata, >100 mg/l (OECD 201)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0
NOELR, (14d), Fish, 1 g/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), Fish, 100 mg/L
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (containing < 3% DMSO-extract), CAS: 72623-86-0
NOELR, (14d), Fish, 1 g/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), Fish, 100 mg/L
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
NOELR, (14d), Fish, 1 g/L
LL50, (4d), Invertebrates, 10 g/L
LL50, (4d), Fish, 100 mg/L
1-Decene, homopolymer, hydrogenated, CAS: 68037-01-4
EL50, (48h), Invertebrates, 1 g/L
EL50, (48h), Algae, 1 g/L
LL50, (96h), Fish, 1 g/L
C14-16-18 Alkyl phenol, CAS: 1190625-94-5
LC50, (96h), Cyprinus carpio, >100 mg/l
EC50, (24h), Daphnia magna, >100 mg/l
EC50, (72h), Pseudokirchneriella subcapitata, >100 mg/l
NOEC, (72h), Pseudokirchneriella subcapitata, 100 mg/l
NOELR, (24h), Daphnia magna, >100 mg/l
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7
NOELR, (14d), Fish, 1 mg/L
LL50, (96h), Invertebrates, 10 g/L
LL50, (96h), Fish, 100 mg/L

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0 Page 13 / 16

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

Substance
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7
Inherently biologically degradable

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

Contains no ingredients with endocrine-disrupting properties.

12.7 Other adverse effects

Ecological data of complete product are not available.
Do not discharge product unmonitored into the environment or into the drainage.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

In according to RoHS!
Coordinate disposal with the authorities if necessary.

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150102
150104
150110* packaging containing residues of or contaminated by hazardous substances

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0 Page 14 / 16

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable



SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0 Page 15 / 16

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	2008/98/EG (2000/532/EC); 2010/75/EU; 2004/42/EG; (EG) 648/2004; (EC) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EWG ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014; (EU) 2019/1148; (EU) 2019/1021, (EU) 2023/707
- Comment on component parts	Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
- Annex XIV (REACH)	According to Annex XIV of Regulation (EC) 1907/2006 (REACH) the product does not contain any substances $\geq 0.1\%$ that are subject to authorisation.
- Annex XVII (REACH)	According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product contains $\geq 0.1\%$ of substances with the following restrictions. 75 According to Annex XVII of Regulation (EC) 1907/2006 (REACH) the product is not subject to any restrictions.
TRANSPORT-REGULATIONS	ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2024)
NATIONAL REGULATIONS (UK):	EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK REACH; GB CLP.
- Observe employment restrictions for people	no
- VOC (2010/75/CE)	not relevant

15.2 Chemical safety assessment

For this product a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H317 May cause an allergic skin reaction.
H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

SWAG Autoteile GmbH
42117 Wuppertal

Date printed 07.08.2024, Revision 07.08.2024

Version 1.0 Page 16 / 16

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
EL50 = Median effective loading
ELINCS = European List of Notified Chemical Substances
EmS = Emergency Schedules
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
IVIS = In vitro irritation score
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
LL50 = Median lethal loading
LQ = Limited Quantities
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV®/TWA = Threshold limit value – time-weighted average
TLV®STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Modified position none