Ferdinand Bilstein GmbH + Co. KG

Date printed 29.10.2019, Revision 29.10.2019



Version 01 Page 1 / 10

		bstance/mixture and of the company/undertaking
1.1	Product identifier	
		febi 170126 Gear oil SAE 75W-80 (GL-4)
		Article number: 170126, 170127, 170134
1.2	Relevant identified uses of the	e substance or mixture and uses advised against
1.2.1	Relevant uses	
		Gearbox oil
1.2.2	2 Uses advised against	
	j	None known.
1.3	Details of the supplier of the s	-
	Company	Ferdinand Bilstein GmbH + Co. KG Wilhelmstr. 47
		58256 Ennepetal / GERMANY
		Phone +49 2333 911-0 Fax +49 2333 911-444
		Homepage www.febi.com
		E-mail info@febi.com
	Address enquiries to	
	Technical information	info@febi.com
	Safety Data Sheet	info@febi.com
1.4	Emergency telephone number	r
	Advisory body	+49 (0)89-19240 (24h) (English)
SEC	TION 2: Hazards identification	
2.1	2.1 Classification of the substance or mixture [REGULATION (EC) No 1272/2008]	
		No classification.
2.2	Label elements	
2.2	Laber elements	The product is required to be labelled in accordance with regulation (EC) No $1272/2009$ (CLD)
	Hazard nictograms	The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP)
	Hazard pictograms	none
	Signal word Hazard statements	none
		none
	Precautionary statements	none
	Special labelling	EUH210 Safety data sheet available on request.
		Contains: Methyl methacrylate, 2-Ethylhexyl methacrylate, Reaction products of bis(4- methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched). EUH208 May produce an allergic reaction.
2.3	Other hazards	
	Physico-chemical hazards	No particular hazards known.
	Environmental hazards	Does not contain any PBT or vPvB substances.

Ferdinand Bilstein GmbH + Co. KG

Date printed 29.10.2019, Revision 29.10.2019

Version 01

Page 2 / 10

SECTION 3: Composition / Information on ingredients

Product-type:

3.2 The product is a mixture.

		Range [%] Substance	
1 - < 5 Bis(nonylphenyl)amine			
			EINECS/ELINCS: 253-249-4, Reg-No.: 01-2119488911-28-XXXX
	GHS/CLP: Aquatic Chronic 4: H413 0,1 - < 1 Methyl methacrylate CAS: 80-62-6, EINECS/ELINCS: 201-297-1, EU-INDEX: 607-035-00-6 CILS/CLP: Flow Liz25 STOT SE 2: LI225 Strip Init 0: LI2/CLP: Flow Liz25 CAS: 80-62-6, EINECS/ELINCS: 201-297-1, EU-INDEX: 607-035-00-6		
			q. 2: H225 - STOT SE 3: H335 - Skin Irrit. 2: H315 - Skin Sens. 1: H317
	1 - < 2,5 Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxid amines, C12-14-alkyl (branched)		yl (branched)
		CAS: -, EINECS/EL	
		GHS/CLP: Acute To	ox. 4: H302 - Eye Dam. 1: H318 - Skin Sens. 1: H317 - Aquatic Chronic 2: H411
	0,1 - < 1	2-Ethylhexyl metha	
			IECS/ELINCS: 211-708-6, EU-INDEX: 607-134-00-4
		GHS/CLP: Skin Ser	ns. 1B: H317 - Aquatic Chronic 3: H412
	Comment on com	ponent parts	Contains less than 3% w/w DMSO-extract (only for mineral oils) Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%. For full text of H-statements and R-phrases: see SECTION 16.
SEC	TION 4: First aid	measures	
4.1	Description of fi	rst aid measures	
	General information		Change soaked clothing.
			Change board of thing.
	Inhalation		Ensure supply of fresh air. In the event of symptoms seek medical treatment.
	Skin contact		In case of contact with skin wash off immediately with plenty of water. Consult a doctor if skin irritation persists.
	Eye contact		Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
	Ingestion		Consult a doctor immediately. Do not induce vomiting. Rinse out mouth and give plenty of water to drink.
4.2	Most important symptoms and effects, both acute and delayed		fects. both acute and delaved
		- ,	Allergic reactions
4.3	Indication of an	Indication of any immediate medical attention and special treatment needed	
			Treat symptomatically.
			Forward this sheet to the doctor.
SEC	TION 5: Fire-fight	ting measures	
5.1	Extinguishing m	nedia	
	Suitable extinguis		foam, dry powder, water spray jet, carbon dioxide
	Extinguishing me	-	Full water jet.
	be used	ula that must not	r uli water jet.
5.2	Special hazards	arising from the	substance or mixture
	-	-	Risk of formation of toxic pyrolysis products.
			Carbon monoxide (CO)
			Sulphur oxides (SOx).
			Nitrogen oxides (NOx).

Ferdinand Bilstein GmbH + Co. KG

Date printed 29.10.2019, Revision 29.10.2019



Version 01 Page

Page 3 / 10

5.3	Advice for firefighters		
		Do not inhale explosion and/or combustion gases. Use self-contained breathing apparatus.	
		Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.	
SEC	TION 6: Accidental release measur	es	
6.1	Personal precautions, protective equipment and emergency procedures		
		High risk of slipping due to leakage/spillage of product. Forms slippery surfaces with water.	
6.2	Environmental precautions		
		Prevent spread over a wide area (e.g. by containment or oil barriers). Do not discharge into the drains/surface waters/groundwater.	
6.3 Methods and material for containment and cleaning up		ment and cleaning up	
		Take up with absorbent material (e.g. oil binder). Dispose of absorbed material in accordance within the regulations.	
6.4	Reference to other sections		
		See SECTION 8+13	
SEC	TION 7: Handling and storage		
7.1	Precautions for safe handling		
		No special measures necessary if used correctly.	
		Use only in well-ventilated areas. Use solvent-resistant equipment.	
		Do not eat, drink or smoke when using this product.	
		After worktime and before work breaks the affected skin areas must be thoroughly cleaned.	
		Use barrier skin cream. Cloths contaminated with product should not be kept in trouser pockets.	
		Take off contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace.	
7.2	Conditions for safe storage, inclu	ding any incompatibilities	
		Keep only in original container. Prevent penetration into the ground.	
		Do not store together with oxidizing agents.	
		Keep container tightly closed. Keep container in a well-ventilated place.	
7.3	Specific end use(s)		
		See product use, SECTION 1.2	

Ferdinand Bilstein GmbH + Co. KG

Date printed 29.10.2019, Revision 29.10.2019



Version 01 Pa

Page 4 / 10

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

not applicable

DNEL

PNEC

Substance		
Bis(nonylphenyl)amine, CAS: 36878-2	0-3	
Industrial, dermal, Long-term - systen	c effects: 5 mg/kg bw/day.	
general population, oral, Long-term -	ystemic effects: 0,25 mg/kg bw/day.	
general population, dermal, Long-tern	- systemic effects: 2,5 mg/kg bw/day.	
Substance		
Bis(nonylphenyl)amine, CAS: 36878-2	0-3	
soil, 263000 mg/kg.		
sediment (seawater), 13200 mg/kg.		
sediment (freshwater), 132000 mg/kg		
sewage treatment plants (STP), 1 mg		
seawater, 0,01 mg/l.		
freshwater, 0,1 mg/l.		

8.2 Exposure controls

-	
Additional advice on system design	Ensure adequate ventilation on workstation. General exposure limit for oil mist should be noted. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,4 mm: Nitrile rubber, >120 min (EN 374-1/-2/-3).
Skin protection	Light protective clothing.
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.
Respiratory protection	not applicable
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

Ferdinand Bilstein GmbH + Co. KG

Date printed 29.10.2019, Revision 29.10.2019



Version 01

Page 5 / 10

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· · · · · · · · · · · · · · · · · · ·	
Form	liquid
Color	yellow
Odor	characteristic
Odour threshold	No information available.
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	No information available.
Flash point [°C]	230
Flammability (solid, gas) [°C]	No information available.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	No information available.
Density [g/ml]	0,85 (DIN 51757) (15 °C / 59,0 °F)
Bulk density [kg/m³]	not applicable
Solubility in water	immiscible
Partition coefficient [n-octanol/water]	No information available.
Viscosity	57,3 mm²/s (40°C)
Relative vapour density determined in air	No information available.
Evaporation speed	No information available.
Melting point [°C]	No information available.
Autoignition temperature [°C]	not applicable
Decomposition temperature [°C]	No information available.

9.2 Other information

No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

See SECTION 10.3.

10.2 Chemical stability

The product is stable under standard conditions.

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

No special measures necessary.

10.5 Incompatible materials

Strong oxidizing agent. Strong basic compounds strong acids

10.6 Hazardous decomposition products

No hazardous decomposition products known.

Ferdinand Bilstein GmbH + Co. KG

Date printed 29.10.2019, Revision 29.10.2019



Version 01

Page 6 / 10

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Substance
2-Ethylhexyl methacrylate, CAS: 688-84-6
LD50, dermal, > 5000 mg/kg bw.
LD50, oral, Rat: > 2000 mg/kg bw.
Methyl methacrylate, CAS: 80-62-6
LD50, oral, Rat: 7872 mg/kg (RTECS).
LD50, dermal, Rabbit: > 5000 mg/kg (RTECS).
LC50, inhalative, Rat: 7093 ppm/4h (Lit.).
LC50, inhalative, Rat: 78000 mg/m ³ (4 h) (RTECS).
Bis(nonylphenyl)amine, CAS: 36878-20-3
LD50, dermal, Rat: >2000 mg/kg (OECD 402).
LD50, oral, Rat: >5000 mg/kg (OECD 401).
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), CAS: -
I D50. oral. Rat: 2000 mg/kg

LD50, oral, Rat: 2000 mg/kg.

Serious eye damage/irritation	Based on the available information, the classification criteria are not fulfilled. Non-irritant. Classification was carried out based on substance-specific concentration limits. The undiluted substance "931-384-6" is an irritant while the 50% formulation in mineral oil was not an irritant.
Skin corrosion/irritation	Toxicological data of complete product are not available. No classification. Calculation method
Respiratory or skin sensitisation	Non-sensitizing. On basis of test data
Specific target organ toxicity — single exposure	Based on the available information, the classification criteria are not fulfilled.
Specific target organ toxicity — repeated exposure	Based on the available information, the classification criteria are not fulfilled.
Mutagenicity	Based on the available information, the classification criteria are not fulfilled.
Reproduction toxicity	Based on the available information, the classification criteria are not fulfilled.
Carcinogenicity	Based on the available information, the classification criteria are not fulfilled.
Aspiration hazard	Based on the available information, the classification criteria are not fulfilled.
General remarks	
	Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

Ferdinand Bilstein GmbH + Co. KG

Date printed 29.10.2019, Revision 29.10.2019



Version 01

Page 7 / 10

SECTION 12: Ecological information

12.1 Toxicity

Substance
2-Ethylhexyl methacrylate, CAS: 688-84-6
LC50, (96h), fish: 2.8 mg/L.
EC50, (72h), Algae: 5,3 mg/L.
EC50, (48h), Daphnia magna: 4.6 mg/L.
NOEC, (72h), Algae: 0.81 mg/L.
NOEC, (21d), Daphnia magna: 0.105 mg/L.
Methyl methacrylate, CAS: 80-62-6
LC50, (96h), fish: 191 mg/l (IUCLID).
EC50, (48h), Daphnia magna: 69 mg/l (IUCLID).
IC50, Pseudokirchneriella subcapitata: 170 mg/l (4 d) (OECD 201).
Bis(nonylphenyl)amine, CAS: 36878-20-3
EC50, (48h), Daphnia magna: >100 mg/l (OECD 202).
LC0, (96h), Brachidanio rerio: 58 mg/l (OECD 203).
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), CAS: -
LC50, (96h), fish: 24 mg/l.
EC50, (48h), Daphnia magna: 91,4 mg/l.

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

Ecological data of complete product are not available. Do not discharge product unmonitored into the environment or into the drainage.

Ferdinand Bilstein GmbH + Co. KG

Date printed 29.10.2019, Revision 29.10.2019



Version 01 Pag

Page 8 / 10

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material c It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

	Product	
		In according to RoHS! Disposal in an incineration plant in accordance with the regulations of the local authorities.
	Waste no. (recommended)	130206*
	Contaminated packaging	
		Uncontaminated packaging may be taken for recycling. Packaging that cannot be cleaned should be disposed of as for product.
	Waste no. (recommended)	150110*
SEC	TION 14: Transport information	
14.1	UN number	
	Transport by land according to ADR/RID	not applicable
	Inland navigation (ADN)	not applicable
	Marine transport in accordance with IMDG	not applicable
	Air transport in accordance with IATA	not applicable
14.2	UN proper shipping name Transport by land according to ADR/RID	NO DANGEROUS GOODS
	Inland navigation (ADN)	NO DANGEROUS GOODS
	Marine transport in accordance with IMDG	NOT CLASSIFIED AS "DANGEROUS GOODS"
	Air transport in accordance with IATA	NOT CLASSIFIED AS "DANGEROUS GOODS"
14.3	Transport hazard class(es) Transport by land according to ADR/RID	not applicable
	Inland navigation (ADN)	not applicable
	Marine transport in accordance with IMDG	not applicable

Air transport in accordance with IATA not applicable

Ferdinand Bilstein GmbH + Co. KG

Date printed 29.10.2019, Revision 29.10.2019



Version 01

Page 9 / 10

14.4	Packing group		
	Transport by land according to ADR/RID	not applicable	
	Inland navigation (ADN)	not applicable	
	Marine transport in accordance with IMDG	not applicable	
	Air transport in accordance with IATA	not applicable	
14.5	Environmental hazards		
	Transport by land according to ADR/RID	no	
	Inland navigation (ADN)	no	
	Marine transport in accordance with IMDG	no	
	Air transport in accordance with IATA	no	
14.6	Special precautions for user		
	Relevant information under SECTION 6 t	to 8.	
14.7	Transport in bulk according to An	nex II of MARPOL and the IBC Code	
	not applicable		
SEC	SECTION 15: Regulatory information		
15.1	1 Safety, health and environmental regulations/legislation specific for the substance or mixture		
	EEC-REGULATIONS	1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2016/2037/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014	
	TRANSPORT-REGULATIONS	ADR (2019); IMDG-Code (2019, 39. Amdt.); IATA-DGR (2019)	
	NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011).	

NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011).
- Observe employment restrictions for people - VOC (2010/75/CE)	Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people. not applicable
• •	

15.2 Chemical safety assessment

SECTION 16: Other information

16.1 Hazard statements (SECTION 03)

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H225 Highly flammable liquid and vapour.

H411 Toxic to aquatic life with long lasting effects.

H318 Causes serious eye damage.

H302 Harmful if swallowed.

H413 May cause long lasting harmful effects to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

H317 May cause an allergic skin reaction.

Ferdinand Bilstein GmbH + Co. KG

Date printed 29.10.2019, Revision 29.10.2019



Version 01 Page 10 / 10

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified Chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value – time-weighted average

TLV®STEL = Threshold limit value - short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Modified position

none