

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

febi 32590 Gear oil 75W - 90
Article number: 32590

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Lubricant

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG
Wilhelmstr. 47
58256 Ennepetal / GERMANY
Phone +49 2333 911-0
Fax +49 2333 911-444
Homepage www.febi.com
E-mail info@febi.com

Address enquiries to

Technical information info@febi.com

Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

Company +49 2333 911-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (EC) No 1272/2008]

No classification.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms none

Signal word none

Hazard statements none

Precautionary statements none

Special labelling EUH210 Safety data sheet available on request.

Contains: Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), Polysulfides, di-tert-Bu. EUH208 May produce an allergic reaction.

2.3 Other hazards

Physico-chemical hazards No particular hazards known.

Environmental hazards Does not contain any PBT or vPvB substances.

Other hazards No particular hazards known.

SECTION 3: Composition / Information on ingredients

Product-type:

3.2 The product is a mixture.

Range [%]	Substance
20 - < 50	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based CAS: 72623-87-1, EINECS/ELINCS: 276-738-4, EU-INDEX: 649-483-00-5, Reg-No.: 01-2119474889-13-XXXX GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) CAS: -, EINECS/ELINCS: 931-384-6 GHS/CLP: Acute Tox. 4: H302 - Eye Dam. 1: H318 - Skin Sens. 1: H317 - Aquatic Chronic 2: H411
1 - < 5	Polysulfides, di-tert-Bu CAS: 68937-96-2, EINECS/ELINCS: 273-103-3, Reg-No.: 01-2119540515-43 GHS/CLP: Skin Sens. 1B: H317 - Aquatic Chronic 3: H412

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
For full text of H-statements and R-phrases: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Change soaked clothing.

Inhalation

Ensure supply of fresh air.
In the event of symptoms seek medical treatment.

Skin contact

In case of contact with skin wash off immediately with plenty of water.
Consult a doctor if skin irritation persists.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Ingestion

Consult a doctor immediately.
Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not be used

Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO)
Sulphur oxides (SOx).
Nitrogen oxides (NOx).

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.
Forms slippery surfaces with water.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. oil binder).
Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures necessary if used correctly.
Use only in well-ventilated areas.
Use solvent-resistant equipment.

Do not eat, drink or smoke when using this product.
After worktime and before work breaks the affected skin areas must be thoroughly cleaned.
Use barrier skin cream.
Cloths contaminated with product should not be kept in trouser pockets.
Take off contaminated clothing and wash before reuse.
Contaminated work clothing should not be allowed out of the workplace.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.
Do not store together with oxidizing agents.
Keep container tightly closed.
Keep container in a well-ventilated place.

7.3 Specific end use(s)

See product use, SECTION 1.2



Ferdinand Bilstein GmbH + Co. KG

Date printed 19.09.2019, Revision 19.09.2019

Version 08. Supersedes version: 07

Page 4 / 11

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance
1-Decene, homopolymer, hydrogenated
CAS: 68037-01-4, EINECS/ELINCS: 500-183-1, Reg-No.: 01-2119486452-34-XXXX
Long-term exposure: 5 mg/m ³ , OSHA PEL

DNEL

Substance
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
Industrial, inhalative, Long-term - local effects: 5.6 mg/m ³ 5.6 mg/m ³ .
Industrial, dermal, Long-term - systemic effects: 1 mg/kg bw/day 5.6 mg/m ³ .
Industrial, inhalative, Long-term - systemic effects: 2.7 mg/m ³ .
general population, oral, Long-term - systemic effects: 0.74 mg/kg bw/day 5.6 mg/m ³ .
Polysulfides, di-tert-Bu, CAS: 68937-96-2
Industrial, dermal, Long-term - systemic effects: 3.33 mg/kg bw/day.
Industrial, inhalative, Long-term - systemic effects: 14.5 mg/m ³ .
general population, dermal, Long-term - systemic effects: 1.66 mg/kg bw/day.
general population, inhalative, Long-term - systemic effects: 2.6 mg/m ³ .

PNEC

Substance
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
oral (food), 9,33 mg/kg.
Polysulfides, di-tert-Bu, CAS: 68937-96-2
soil, 1513 mg/kg soil dw 4.51 mg/L.
sediment (seawater), 0.094 mg/kg sediment dw 4.51 mg/L.
sediment (freshwater), 0.94 mg/kg sediment dw 4.51 mg/L.
sewage treatment plants (STP), 4.51 mg/L 4.51 mg/L.
seawater, 0.024 µg/L.
freshwater, 0.24 µg/L.

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. General exposure limit for oil mist should be noted. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,4 mm: Nitrile rubber, >120 min (EN 374-1/-2/-3).
Skin protection	Light protective clothing.
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.
Respiratory protection	not applicable
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	liquid
Color	brown
Odor	characteristic
Odour threshold	No information available.
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	No information available.
Flash point [°C]	210 (EN ISO 2592 (COC))
Flammability (solid, gas) [°C]	No information available.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	No information available.
Density [g/ml]	0,86 (DIN 51757) (15 °C / 59,0 °F)
Bulk density [kg/m³]	not applicable
Solubility in water	miscible
Partition coefficient [n-octanol/water]	No information available.
Viscosity	113,9 mm ² /s (40°C) (DIN 51562)
Relative vapour density determined in air	No information available.
Evaporation speed	No information available.
Melting point [°C]	No information available.
Autoignition temperature [°C]	not applicable
Decomposition temperature [°C]	No information available.

9.2 Other information

No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

See SECTION 10.3.

10.2 Chemical stability

The product is stable under standard conditions.

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

10.4 Conditions to avoid

No special measures necessary.

10.5 Incompatible materials

Strong oxidizing agent.
Strong basic compounds
strong acids

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product
inhalative, Based on the available information, the classification criteria are not fulfilled.:
dermal, Based on the available information, the classification criteria are not fulfilled.:
ATE-mix, oral, > 5000 mg/kg bw.
Substance
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
LD50, dermal, Rabbit: >= 2000 mg/kg (OECD 402).
LD50, oral, Rat: >= 5000 mg/kg (OECD 401).
LC50, inhalative, Rat: >= 5,53 mg/l (OECD 403).
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
LD50, oral, Rat: 2000 mg/kg.
Polysulfides, di-tert-Bu, CAS: 68937-96-2
LD0, dermal, Rat: 2000 mg/kg bw (OECD 402).
LD0, oral, Rat: 2000 mg/kg bw (OECD 401).

Serious eye damage/irritation	Based on the available information, the classification criteria are not fulfilled. Non-irritant. Classification was carried out based on substance-specific concentration limits.
Skin corrosion/irritation	Toxicological data of complete product are not available. No classification. Calculation method
Respiratory or skin sensitisation	Non-sensitizing. On basis of test data
Specific target organ toxicity — single exposure	Based on the available information, the classification criteria are not fulfilled.
Specific target organ toxicity — repeated exposure	Based on the available information, the classification criteria are not fulfilled.
Mutagenicity	Based on the available information, the classification criteria are not fulfilled.
Reproduction toxicity	Based on the available information, the classification criteria are not fulfilled.
Carcinogenicity	Based on the available information, the classification criteria are not fulfilled.
Aspiration hazard	Based on the available information, the classification criteria are not fulfilled.
General remarks	Toxicological data of complete product are not available. The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

SECTION 12: Ecological information

12.1 Toxicity

Product
Based on the available information, the classification criteria are not fulfilled.:
Substance
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, CAS: 72623-87-1
EL50, (24h), Daphnia magna: >10000 mg/l (OECD).
LL50, (96h), Pimephales promelas: >100 mg/l (OECD).
NOEL, (72h), Pseudokirchneriella subcapitata: >100 mg/l (OECD).
NOEL, (21d), Daphnia magna: 10 mg/l (OECD).
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
LC50, (96h), fish: 24 mg/l.
EC50, (48h), Daphnia magna: 91,4 mg/l.
Polysulfides, di-tert-Bu, CAS: 68937-96-2
LC50, (96h), Danio rerio: >0.088 mg/L (OECD 203).
EC50, (72h), Pseudokirchneriella subcapitata: 2.45 mg/L (OECD 201).
EC50, (24h), Daphnia magna: >0.27 mg/L (OECD 202).

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material c It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

In according to RoHS!
Disposal in an incineration plant in accordance with the regulations of the local authorities.

Waste no. (recommended)

130205* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150110*

SECTION 14: Transport information

14.1 UN number

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

Ferdinand Bilstein GmbH + Co. KG

Date printed 19.09.2019, Revision 19.09.2019

Version 08. Supersedes version: 07

Page 10 / 11

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2016/2037/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014

TRANSPORT-REGULATIONS ADR (2019); IMDG-Code (2019, 39. Amdt.); IATA-DGR (2019)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011).

- Observe employment restrictions for people Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.

- VOC (2010/75/CE) not applicable

15.2 Chemical safety assessment

SECTION 16: Other information

16.1 Hazard statements (SECTION 03)

H411 Toxic to aquatic life with long lasting effects.
H318 Causes serious eye damage.
H302 Harmful if swallowed.
H412 Harmful to aquatic life with long lasting effects.
H317 May cause an allergic skin reaction.
H304 May be fatal if swallowed and enters airways.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
ELINCS = European List of Notified Chemical Substances
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV@TWA = Threshold limit value – time-weighted average
TLV@STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Modified position none