EUROLUB
MULTITEC 5W-30

Description

MULTITEC 5W-30 is a top-of-the-range product for petrol and diesel engines in passenger cars, including those fitted with turbochargers in cars and vans. Excellent cold-start performance ensures optimum lubrication reliability during the cold-start phase. It reliably withstands extreme stresses and high temperatures under all operating conditions. It guarantees extremely high wear protection and significantly reduced friction losses.

Fully backward compatible with Ford M2C913-A, B and C.

Can be used with

ACEA A5/B5
API SL/CF
Ford WSS-M2C913-D (überdeckt 913-A/-B/-C)
Renault RN0700
Jaguar Land Rover STJLR.03.5003
VWC 53036

Delivery

Art.-No. 214001	12 x 1 Liter	bottle
Art.-No. 214005	4 x 5 Liter	can
Art.-No. 214020	20 Liter	can
Art.-No. 214060	60 Liter	drum
Art.-No. 214208	208 Liter	drum
Art.-No. 214100	Container	800 – 3.000 litre
Art.-No. 214000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.849
Viscosity at 40°C	mm²/s	DIN 51 562	59.0
Viscosity at 100°C	mm²/s	DIN 51 562	10.2
Viscosityindex (VI)	-	DIN ISO 2909	163
Flash point (COC)	°C	DIN ISO 2592	234
Pourpoint	°C	DIN ISO 3016	-33

Die angegebenen Daten können Änderungen unterliegen. Betriebsvorschriften des Herstellers beachten. Durch Weiterentwicklung von Produkt und Produktion bedingte Datenänderungen bleiben vorbehalten. Diese Angaben sollen das Produkt beschreiben und haben somit nicht die Bedeutung, bestimmte Eigenschaften zuzusichern. Eine Verbindlichkeit kann hieraus nicht abgeleitet werden.

KLIMANEUTRALES UNTERNEHMEN certified by Fokus Zukunft