

EUROLUB TURBO STAR 15W-40

Description

TURBO STAR 15W-40 is a multigrade engine oil for diesel and petrol engines. The SAE 15W-40 viscosity grade ensures reliable cold starts all year round and high-temperature stability, even under extreme conditions. Shear-stable additives ensure that the SAE 15W-40 viscosity grade is maintained throughout the entire service life of the oil. Our carefully selected combination of high-quality base oils and additives provides excellent wear protection and outstanding engine cleanliness; the formation of black sludge is prevented.

Can be used with

API CF-4/SJ
MB 228.1
MAN 271
Volvo VDS

Delivery

Art.-No. 340001	12 x 1 Liter	bottle
Art.-No. 340005	4 x 5 Liter	can
Art.-No. 340020	20 Liter	can
Art.-No. 340060	60 Liter	drum
Art.-No. 340208	208 Liter	drum
Art.-No. 340100	Container	800 – 3.000 litre
Art.-No. 340000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.863
Viscosity at 40°C	mm ² /s	DIN 51 562	103.0
Viscosity at 100°C	mm ² /s	DIN 51 562	15.3
Viscosityindex (VI)	-	DIN ISO 2909	150
Flash point (COC)	°C	DIN ISO 2592	220
Pourpoint	°C	DIN ISO 3016	-33