

EUROLUB GEAR UNI 80W-90

Description

GEAR UNI 80W-90 is a high-alloy multi-grade gear oil for manual gearboxes and axle drives; its EP additives ensure a stable lubricating film even under the most severe loads on gear flanks and during sliding contact, thereby reducing wear.

Can be used with

API GL-5
MIL PRF – 2105D
MAN 342 Typ M2
ZF TE-ML 05A/12E/16B/17B/19B/21A

Delivery

Art.-No. 365001	12 x 1 Liter	can
Art.-No. 365005	4 x 5 Liter	can
Art.-No. 364020	20 Liter	can
Art.-No. 364060	60 Liter	drum
Art.-No. 364208	208 Liter	drum
Art.-No. 364100	Container	800 – 3.000 litre
Art.-No. 364000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.892
Viscosity at 40°C	mm ² /s	DIN 51 562	140.0
Viscosity at 100°C	mm ² /s	DIN 51 562	14.1
Viscosityindex (VI)	-	DIN ISO 2909	98
Flash point (COC)	°C	DIN ISO 2592	230
Pourpoint	°C	DIN ISO 3016	-30