

## EUROLUB GEAR LSL 75W-90

### Description

High-performance transmission oil for manual and final drive gearboxes with LS suitability (= Limited Slip). A multi-purpose transmission oil for use in conventional manual and final drive gearboxes in passenger cars, off-road vehicles and commercial machinery. It can also be used in final drive gearboxes fitted with multi-plate limited-slip differentials.

### Can be used with

API GL-4 / GL-5 / GL-5 LS (Limited Slip)  
MAN 342 Typ M1/M2/M3  
MACK GO-J/GO-J Plus  
Scania STO 1:0

BMW 83 22 9 407 768  
Ford 1 347 488  
GM 93165290  
Opel 19 40 182  
Vauxhall 93165290  
VW G 052 145 A1

### Delivery

|                 |              |                   |
|-----------------|--------------|-------------------|
| Art.-No. 383001 | 12 x 1 Liter | bottle            |
| Art.-No. 383020 | 20 Liter     | can               |
| Art.-No. 383060 | 60 Liter     | drum              |
| Art.-No. 383208 | 208 Liter    | drum              |
| Art.-No. 383100 | Container    | 800 – 3.000 litre |
| Art.-No. 383000 | Bulk         | from 3.001 litre  |

### Technical Data

| Data                | Unit               | Method       | Value |
|---------------------|--------------------|--------------|-------|
| Density at 15°C     | kg/L               | DIN 51 757   | 0.879 |
| Viscosity at 40°C   | mm <sup>2</sup> /s | DIN 51 562   | 83.0  |
| Viscosity at 100°C  | mm <sup>2</sup> /s | DIN 51 562   | 14.8  |
| Viscosityindex (VI) | -                  | DIN ISO 2909 | 188   |
| Flash point (COC)   | °C                 | DIN ISO 2592 | 180   |
| Pourpoint           | °C                 | DIN ISO 3016 | -39   |