

EUROLUB CLEANTEC DXS 5W-30

Description

CLEANTEC DXS 5W-30 is a high-tech, low-friction engine oil based on synthetic technology. It is a fuel-efficient engine oil, specifically designed for modern passenger cars that require the GM dexos1™ Gen. 3 specification. CLEANTEC DXS 5W-30 minimises the so-called LSPI effect (Low Speed Pre-Ignition) and thereby ensures a longer engine life.

Can be used with

API SQ (RC)
ILSAC GF-7A
GM dexos1™ Gen. 3
Chrysler MS-6395
Chrysler MS-13340
Ford WSS-M2C929-A, -946-A/-B1, Ford WSS-M2C961-A1
GM 6094M
Fiat 9.55535-CR1
VWC 53034

Delivery

Art.-No. 385001	12 x 1 Liter	bottle
Art.-No. 385005	4 x 5 Liter	can
Art.-No. 385020	20 Liter	can
Art.-No. 385060	60 Liter	drum
Art.-No. 385208	208 Liter	drum
Art.-No. 385100	Container	800 – 3.000 litre
Art.-No. 385000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.852
Viscosity at 40°C	mm ² /s	DIN 51 562	64.3
Viscosity at 100°C	mm ² /s	DIN 51 562	10.8
Viscosityindex (VI)	-	DIN ISO 2909	160
Flash point (COC)	°C	DIN ISO 2592	234
Pourpoint	°C	DIN ISO 3016	-39