

EUROLUB SYNT 5W-40

Description

The significantly improved quality of SYNT 5W-40 engine oil is due in particular to its further enhanced wear protection and improved engine cleanliness, even with extended oil change intervals. SYNT 5W-40 is suitable as a high-performance, low-friction engine oil for demanding engines. It is recommended for petrol and diesel engines in passenger cars, including turbocharged versions and direct-injection engines, under all operating conditions (excluding PD, WIV, DPF).

Can be used with

ACEA A3 / B4
API SN / CF
VW 502.00 / 505.00
MB 229.3 / 226.5
BMW Longlife-01
Porsche A40
Renault RN0700 / RN0710
GM LL-B-025
Fiat 9.55535-M2
PSA B71 2296

Delivery

Art.-No. 316001	12 x 1 Liter	bottle
Art.-No. 316005	4 x 5 Liter	can
Art.-No. 316020	20 Liter	can
Art.-No. 316060	60 Liter	drum
Art.-No. 316208	208 Liter	drum
Art.-No. 316100	Container	800 – 3.000 litre
Art.-No. 316000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.849
Viscosity at 40°C	mm ² /s	DIN 51 562	85.7
Viscosity at 100°C	mm ² /s	DIN 51 562	14.4
Viscosityindex (VI)	-	DIN ISO 2909	175
Flash point (COC)	°C	DIN ISO 2592	240
Pourpoint	°C	DIN ISO 3016	-36