

EUROLUB GT 10W-40

Description

GT 10W-40 is a low-friction engine oil; its base, derived from modern refining technology, combined with high-quality lubricant components and shear-stable additives, ensures that the specified viscosity grade is maintained throughout the oil's service life. Reliable cold starts even at low temperatures and high-temperature resistance under heavy loads are guaranteed. Detergent additives prevent deposits; pistons and valves remain clean, guaranteeing the maximum permissible oil retention time. GT 10W-40 is recommended for petrol and diesel engines in passenger cars, including turbo-diesel and catalytic converter versions (excluding PD, WIV, DPF).

Can be used with

ACEA A3 / B4
API SL / CF
MB 229.1
VW 501.01 / 505.00

Delivery

Art.-No. 337001	1 Liter	can
Art.-No. 337020	20 Liter	can
Art.-No. 337060	60 Liter	drum
Art.-No. 337208	208 Liter	drum
Art.-No. 337100	Container	800 – 3.000 litre
Art.-No. 337000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Densitv at 15°C	kg/L	DIN 51 757	0.867
Viscosity at 40°C	mm ² /s	DIN 51 562	98.0
Viscositv at 100°C	mm ² /s	DIN 51 562	14.4
Viscosityindex (VI)	-	DIN ISO 2909	154
Flash point (COC)	°C	DIN ISO 2592	226
Pourpoint	°C	DIN ISO 3016	-30