

# Product information

AIC Germany Gear oil CVT

AIC No. 70777

## Description

High-performance automatic transmission oil, specially formulated for use in the latest generation of CVT transmissions. High ageing and oxidation stability as well as best protection against foaming. Tried and tested, especially in Autotronic transmissions, but also in many continuously variable automatic transmissions from various manufacturers.

**Observe the manufacturer's instructions!**

## AIC Germany also recommends this product for vehicles for which the following specifications are required:

Ford CVT23 • Ford CVT30 • Ford Mercon C • Honda HMMF • Jeep NS-2 • Jeep CVTF+4 • MB 236.20 • Mini Cooper (EZL 799) • Mitsubishi CVTF-J1 • Mitsubishi CVTF-J4 • Nissan CVT NS-2 Fluid • Subaru NS-2 • Suzuki CVT Green1 • Suzuki NS-2 • Suzuki TC • Toyota TC • Subaru Lineartronic CVTF • VW G 052 180 • VW G 052 516 • Dodge NS-2 • Dodge CVTF+4 • GM/Saturn DEX-CVT

Characteristic data	Density at 15 °C	0,855 g/cm <sup>3</sup>
		DIN 51757
Viscosity at 40 °C	36,0 mm <sup>2</sup> /s	
	ASTM D 7042-04	
Viscosity at 100 °C	7,5 mm <sup>2</sup> /s	
	ASTM D 7042-04	
Viscosity at -40 °C (Brookfield)	<= 20000 mPas	
	ASTM D 2983-09	
Viscosity index	180	
	DIN ISO 2909	
Flash point	200 °C	
	DIN ISO 2592	
Pourpoint	-45 °C	
	DIN ISO 3016	
Colourindex (ASTM)	L 2,0	
	DIN ISO 2049	

Available container	1l Plastic tin	70777
		D-GB-F-IT-NL-DA-RUS-LT-CZ