

Engine oil

ProfiPower 4CAR 0W30 EXTREME PROTECT TECH VW

Characteristic

- Compatible with DPF filters
- Maximises short and long term engine performance
- Fuel economy
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures
- Mid SAPS formulation

Application

PROFIPOWER 4CAR 0W30 EXTREME PROTECT TECH VW OIL is designed for use in modern, low-emission petrol and diesel engines in passenger cars, off-road and light commercial vehicles in which extended intervals between oil changes is expected.

Standards, specifications

SAE: 0W/30

ACEA: C3

VW 504 00 / 507 00

Porsche C30

MB 229.52

BMW LL-04



Physical and chemical properties

Specifications	PDS_PROFIPOWER 4CAR 0W30 EXTREME PROTECT TECH VW
Kinematic viscosity at 100°C, [mm ² /s]	12,0
Viscosity Index	190
Pour point, [°C]	-48
Flash point, [°C]	200
TBN, [mg KOH/g]	8,0
Sulphated ash, [%]	0,7

Note: The above values of physico - chemical parameters are typical values. The actual values are placed in the judgment laboratory attached to each batch of product)

Is similar to:

Mobil 1 ESP 0W-30
 Castrol EDGE Professional Longlife III 0W-30
 Total Quartz Ineo Long Life 0W30
 Shell Helix Ultra Professional AV-L 0W-30



- ▼ **The production of PROFIPower 4CAR 0W30 EXTREME PROTECT TECH VW oils uses advanced technology of oil according to the most rigorous standards to ensure optimum engine protection in the heaviest operation conditions.**
- ▼ **Quality confirmed by tests in specialized laboratories.**
- ▼ **Production of PROFIPower 4CAR 0W30 EXTREME PROTECT TECH VW goes in precisely defined technological process and multistage quality control assurance.**