

Gear oil

ProfiPower 4GEAR 75W80 MANUAL ULTRA PROTECT GL-4/GL-5

Characteristic

- Excellent extreme pressure and antiwear properties
- Reduces the wear of transmission components
- Excellent antifoam, anticorrosion, antitrust properties
- Very low loss in viscosity through shear
- Allows easy starting at low temperatures

Application

Universal, semisynthetic, multiseasonal oil intended for manual gears of vehicles. Due to AW and EP additives content PROFIPOWER 4GEAR 75W80 MANUAL ULTRA PROTECT GL-4/GL-5 guarantees very good anti-wear properties. For lubricating mechanical gearboxes (synchronized or not) and axles in cars and trucks as well as construction and agricultural machinery in the most heavy-duty conditions where API GL-5 and SAE 75W/80 are required.

Standards, specifications

API: GL-5/GL-4

SAE: 75W/80

MAN:341 Type Z4

MAN: 341 Type E3

ZF TE-ML 02L/16K

DAF; Iveco; Renault; Volvo



Physical and chemical properties

Specifications	PROFIPOWER 4GEAR 75W80 MANUAL ULTRA PROTECT GL-4_GL-5
Kinematic viscosity at 100°C, [mm ² /s]	10,5
Viscosity Index	145
Pour point, [°C]	-45
Flash point, [°C]	210
Note: The above values of physico - chemical parameters are typical values. The actual values are placed in the judgment laboratory attached to each batch of product)	

- ✓ The production of PROFIPOWER 4CAR 10W40 FULL CLEAN oils uses advanced technology of oil according to the most rigorous standards to ensure optimum engine protection in the heaviest operation conditions.
- ✓ Quality confirmed by tests in specialized laboratories .
- ✓ Production of PROFIPOWER 4CAR 10W40 FULL CLEAN goes in precisely defined technological process and multistage quality control assurance.

